



Auto Scrub/UHS Cleaner

auto scrub pad

PRODUCT SPECIFICATIONS

1.0 Description

The Auto Scrub Pad is constructed of polyester fibers in an open texture nonwoven fabrication and is designed for cleaning. Abrasive particles are dispersed throughout and bonded to the nonwoven construction with a durable adhesive.

2.0 Properties

| Property | Value |
|----------------------|-------------------------------|
| Thickness | 1 in 26 mm |
| Weight | 28 osy 949 gsm |
| Fiber Type | Recycled Polyester |
| Binder System | Cross-linkable water based |
| Binder Application | Spray/Dip |
| Abrasive Application | Spray/Dip |
| Abrasive | Yes |
| Color | Gray |
| Pack | 5 per case* |

*27" also available in 2 per case

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact Americo with any questions or concerns.

Americo Manufacturing Company, Inc.

1-800-849-6287

www.americomfg.com

© 2017

Rev. 0428/17
Auto Scrub / UHS Cleaner Product Specifications

3.0 Use

Use with neutral floor cleaning solutions to remove soil and black heel marks. This pad is also used to clean soiled hard surface floors such as concrete when used with appropriate cleaning chemicals. While this pad is designed for auto scrubbers, it is also ideal for use on machines speeds up to 1500 rpm.

4.0 Construction

The Auto Scrub Pad is constructed of polyester fibers and synthetic adhesives that will not be significantly affected by water, detergents and cleaners normally used for floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides.

5.0 Labeling

Labeling is to clearly identify product, size, and quantity. Americo brand or private label is available for this product.

6.0 Environmental Initiatives

- Polyester fiber used in our pads come from 100% post consumer and industrial recycled waste product.
- Water Based Latex Resins are used in the manufacturing process. No phenol-formaldehyde resins are used in our binding process.
- Shipping cartons contain at least 45% recycled material.
- Plant is operating under EPA approved Clean Air Permit.
- In-house water treatment has reduced our waste water flow by 83%.

7.0 Directions for Use

Use pad until soil and heel marks are removed from floor. Pick up cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic. Follow use with an Americo polishing pad to achieve high gloss.

8.0 Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil.

9.0 Sizes

| Disc Size (Diameter) (O.D. ± 0.06 inch) | Center Hole |
|--|-------------|
| 11 inch | 3.25 inch |
| 12 inch | 3.25 inch |
| 13 inch | 3.25 inch |
| 14 inch | 3.25 inch |
| 15 inch | 3.25 inch |
| 16 inch | 3.25 inch |
| 17 inch | 3.25 inch |
| 18 inch | 3.25 inch |
| 19 inch | 3.25 inch |
| 20 inch | 3.25 inch |
| 21 inch | 3.25 inch |
| 22 inch | 3.25 inch |
| 23 inch | 3.25 inch |
| 24 inch | 3.25 inch |
| 27 inch | 3.25 inch |

Additional sizes available.

Check for availability on additional center hole dimensions.