



Maroon Conditioning Pad

THIN LINE

PRODUCT SPECIFICATIONS

1.0 Description

The Maroon Conditioning Pad is constructed of polyester fibers in a textured nonwoven fabrication. Abrasive particles are distributed throughout and bonded to the nonwoven construction with a sturdy adhesive.

2.0 Properties

Property	Value
Thickness	0.43 in 11 mm
Weight	34 osy 1153 gsm
Fiber Type	Recycled Polyester
Binder System	Cross-linkable water based
Binder Application	Spray/Dip
Abrasive Application	Spray/Dip
Abrasive	Yes
Color	Maroon
Pack	10 per case

3.0 Use

Use between laying new coats of urethane on wood floors to create a light scratch pattern on the previous coat. It can also be used for light cleaning of wood floors. For use on standard electric floor machines or automatic scrubbers. Ideal for use on machines speeds up to 350 rpm.

4.0 Construction

The Maroon Conditioning Pad is constructed of polyester fibers and synthetic adhesives that will not be notably affected by water or cleaners normally used for floor maintenance. The abrasives used in this product are synthetic material. This pad has been designed for use on both sides.

5.0 Labeling

Labeling is to clearly identify product, size, and quantity. Americo brand or private label is available for this product.

6.0 Environmental Initiatives

- Polyester fiber used in our pads come from 100% post consumer and industrial recycled waste product.
- Water Based Latex Resins are used in the manufacturing process. No phenol-formaldehyde resins are used in our binding process.
- Shipping cartons contain at least 45% recycled material.
- Plant is operating under EPA approved Clean Air Permit.

7.0 Directions for Use

The Maroon Conditioning pad has been specifically designed for abrading floors between coats of urethane finish. First, make sure the floor's surface is completely dry by following the finish manufacturer's directions. Next, dust mop or sweep floor to make sure it is free of dust and debris before the next step of using the Maroon Conditioning pad, on a low speed machine, to produce a light scratch pattern on floor's surface. Pick up the residual dust generated with a mop, wet vacuum or auto scrubber. Rinse the floor and let dry prior to re-coating.

8.0 Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

9.0 Sizes

Disc Size (Diameter) (O.D. ± 0.06 inch)	Center Hole
12 inch.....	3.25 inch
13 inch.....	3.25 inch
14 inch.....	3.25 inch
15 inch.....	3.25 inch
16 inch.....	3.25 inch
17 inch.....	3.25 inch
18 inch.....	3.25 inch
19 inch.....	3.25 inch
20 inch	3.25 inch

Rectangular Size

- 12 inch x 18 inch
- 14 inch x 20 inch
- 14 inch x 24 inch
- 14 inch x 28 inch
- 14 inch x 32 inch

Additional sizes available.

Check for availability on additional center hole dimensions.



Full Cycle® Products are certified by Green Seal® for Environmental Innovation based on faster biodegradation in landfill conditions and 100% recycled content/natural fiber. GreenSeal.org/GS20

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact Americo with any questions or concerns.

Americo Manufacturing Company, Inc.

1-800-849-6287

www.americomfg.com

© 2021

Rev. 2/02/21
Maroon Conditioning Product Specifications